

GENIEMAT[®] FF03NP

SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FF03NP

DESCRIPTION: Robust reduced sound transmission mat made from 94% recycled rubber content used when superior sound control is required in multifamily housing, high-rises, or commercial buildings.

FEATURES AND BENEFITS:

- Significantly reduces impact sound
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- Easy to install and rolls out quickly
- Will not fail under high point loads

DIMENSION: Rollgood: 1.2 m wide, 22.9 m long (4' wide, 75' long)

THICKNESS: nom. 3 mm (1/8") (2.5mm +/- 0.5mm)

ROLL WEIGHT: 60 kg/roll (133 lb/roll)

ROLL AREA: 27.9 m² (300 ft²)

ROLLS/PALLET: 15

LEAD TIME: 2-3 weeks after receipt of order

TECHNICAL DATA

SHEET WEIGHT: 3.14 kg/m² (0.64 lb/ft²)

TYPE A HARDNESS (ASTM D2240): 40 durometer

TEMPERATURE STABILITY: -40°C to +115°C (-40°F to +240°F)

Contact Us:



VK ASIA
Innovative Building Materials

Mobile: 098 132 0674

Email: vkasiaco@gmail.com

Zalo Contact:



CONTACT Us

For Your Project Specific Questions

Asia Pacific +65 8452 6865 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444

E. info@pliteq.sg

© Pliteq Asia Pacific PTE LTD. 2020.

03.20
*™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.sg