

GENIEMAT[®] FF05NP

SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FF05NP

DESCRIPTION: Robust reduced sound transmission mat made from 94% recycled rubber content used when superior sound control is required in multifamily housing, high-rises, or commercial buildings.

FEATURES AND BENEFITS:

- Significantly reduces impact sound
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- Easy to install and rolls out quickly
- Will not fail under high point loads

DIMENSION: Rollgood: 1.2 m wide, 9.1 m long (4' wide, 30' long)

THICKNESS: nom. 5 mm (3/16")

ROLL WEIGHT: 43 kg/roll (95 lb/roll)

ROLL AREA: 11.2 m² (120 ft²)

ROLLS/PALLET: 20

LEAD TIME: 2-3 weeks after receipt of order

TECHNICAL DATA

SHEET WEIGHT: 5.05 kg/m² (1.03 lb/ft²)

TYPE A HARDNESS (ASTM D2240): 40 durometer

TEMPERATURE STABILITY: -40°C to +115°C (-40°F to +240°F)

CONTACT US

For Your Project Specific Questions

Asia Pacific +65 8452 6865 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444

E. info@pliteq.sg

Contact Us:



VK ASIA
Innovative Building Materials

Mobile: 098 132 0674

Email: vkasiaco@gmail.com

Zalo Contact:



www.pliteq.sg