



SAI-UNL

Product Specifications

PRODUCT NAME	SAI-UNL03
DESCRIPTION	<ul style="list-style-type: none"> Eco-friendly rubber sheets produced with recycled rubber Used in a wide range of buildings to protect sensitive areas from noise sources or to contain noise sources within their areas Absorbs the flow of sound generated in Residential & Commercial buildings
THICKNESS	3 mm
DENSITY	$\geq 800 \text{ kg/m}^3$
NATURE OF PACKING	Rolls
ROLL SIZE	1.2 m x 10 m
WEIGHT OF EACH ROLL	Approx 30 kg
SALIENT FEATURES	<ul style="list-style-type: none"> ✓ Easy and quick to install ✓ Low deflection under high loads ✓ No breakage or movement when under load ✓ Resistant to ageing, rot-proof, resistant to chemicals and odour free

Technical Data

Acoustic parameters determined using Concrete Slab and Floor covering

HARDNESS (SHORE A) As per ISO 7619-1	55 - 60
TENSILE STRENGTH	$> 0.5 \text{ N/mm}^2$
ELONGATION AT BREAK	$> 70 \%$
IMPACT INSULATION CLASS (IIC)	55 - 60
AIRBORNE SOUND INSULATION (R_w)	55 dB – 60 dB
IMPACT IMPROVEMENT (ΔL_w)	Upto 21 dB
IMPACT SOUND INSULATION (L'_{nTw})	55 dB – 60 dB
TEMPERATURE STABILITY	- 40°C to +120°C

Contact Us:



Mobile: 098 132 0674
Email: vkasiaco@gmail.com

Zalo Contact:



SUPER ACOUSTICS INSULATION
UAE | QATAR | OMAN | KSA | INDIA

